

DESCRIPTION

Jumbo SDX 15W40 CF-4 provides reliable engine protection of today's diesel engines operating in severe application.

APPLICATIONS

- Naturally aspirates and turbo-charged diesel powered equipment from European, Japanese, and American manufacturers.
- On-Highway light and heavy-duty trucking.
- Off-Highway industries including: construction, mining, quarrying, and agriculture.

BENEFITS

- Oxidation stability that reduces sludge build up and viscosity increase.
- Effective anti-wear and anti-scuff properties that extend engine life and reduce maintenance costs.
- Good soot dispersion that reduces oil consumption and wear.
- Balanced detergency/dispersancy that keeps engines cleaner.
- Exceptional low-temperature flow properties helps speed cold starts.

TYPICAL PROPERTIES

Characteristic	15W40
SAE Grade	15W40
Specific Density @ 15°C	0.8780
Kinematic Viscosity @ 40°C, cSt	114.32
Kinematic Viscosity @ 100°C, cSt	14.0
Viscosity Index	125
Colour, ASTM	L 2.0
Flash Point COC, °C	224
Total Base Number, mgKOH/g,	9

PACKAGING

200 Liter – Drum



DESCRIPTION

Jumbo SDX 15W40 CI-4 is high performance diesel engine oil recommended for modern direct injection and turbocharged engine.

APPLICATIONS

- Naturally aspirates and turbo-charged diesel powered equipment from European, Japanese, and American manufacturers.
- On-Highway light and heavy-duty trucking.
- Off-Highway industries including: construction, mining, quarrying, and agriculture.
- Suitable for Common rail diesel engine.

BENEFITS

- Oxidation stability that reduces sludge build up and viscosity increase.
- Effective anti-wear and anti-scuff properties that extend engine life and reduce maintenance costs.
- Superior soot dispersion that reduces oil consumption and wear.
- Balanced detergency/dispersancy that keeps engines cleaner.
- Exceptional low-temperature flow properties helps speed cold starts.

MEET REQUIREMENTS

API: CI-4, CH-4, SL, SJ.

JASO DH-1

ACEA E7-16, MAN 3275, Volvo VDS-3, Deutz DQC-III, Deutz DQC-II.

MTU 2.0, Mack EO-N, Mack EO-M+, Renault RLD-2, Global DHD-1.

Cummins CES 20078, Cummins CES 20077, DDC 93K215.

Caterpillar ECF-2, Caterpillar ECF-1a.

TYPICAL PROPERTIES

Characteristic	15W40
SAE Grade	15W40
Specific Density @ 15°C	0.8830
Kinematic Viscosity @ 100°C, cSt	13.27
Viscosity Index	132
Colour, ASTM	L 3.5
Flash Point COC, °C	236
Total Base Number, mgKOH/g,	11.81

PACKAGING

200 Liter – Drum



DESCRIPTION

Jumbo SDX 40 CD provides reliable engine protection of today's diesel engines operating in severe application.

APPLICATIONS

- Naturally aspirates and turbo-charged diesel powered equipment from European, Japanese, and American manufacturers.
- On-Highway light and heavy-duty trucking.
- Off-Highway industries including: construction, mining, quarrying, and agriculture.

BENEFITS

- Oxidation stability that reduces sludge build up and viscosity increase.
- Effective anti-wear and anti-scuff properties that extend engine life and reduce maintenance costs.
- Good soot dispersion that reduces oil consumption and wear.
- Balanced detergency/dispersancy that keeps engines cleaner.

TYPICAL PROPERTIES

Characteristic	40
SAE Grade	40
Specific Density @ 15°C	0.8780
Kinematic Viscosity @ 100°C, cSt	14.43
Viscosity Index	98
Colour, ASTM	L 3.0
Flash Point COC, °C	234

PACKAGING

200 Liter – Drum, 18 USQT - Pail



DESCRIPTION

Jumbo SDX 40 CF/SF provides reliable engine protection of today's diesel engines operating in severe application.

APPLICATIONS

- Naturally aspirates and turbo-charged diesel powered equipment from European, Japanese, and American manufacturers.
- On-Highway light and heavy-duty trucking.
- Off-Highway industries including: construction, mining, quarrying, and agriculture.

BENEFITS

- Oxidation stability that reduces sludge build up and viscosity increase.
- Effective anti-wear and anti-scuff properties that extend engine life and reduce maintenance costs.
- Good soot dispersion that reduces oil consumption and wear.
- Balanced detergency/dispersancy that keeps engines cleaner.

TYPICAL PROPERTIES

Characteristic	40
SAE Grade	40
Specific Density @ 15°C	0.8820
Kinematic Viscosity @ 40°C, cSt	118.53
Kinematic Viscosity @ 100°C, cSt	14.82
Viscosity Index	101
Colour, ASTM	L 3.0
Flash Point COC, °C	208
Total Base Number, mgKOH/g,	10

PACKAGING

200 Liter – Drum



DESCRIPTION

Jumbo SDX 40 CF-2 is heavy-duty diesel engine oil specially designed to lubricate diesel engines requiring API CF-2 classification.

APPLICATIONS

- Mixed fleets of diesel engines.
- Small diesel engines in marine services.
- Generator sets.

BENEFITS

- Oxidation stability that reduces sludge build up and viscosity increase.
- Effective anti-wear and anti-scuff properties that extend engine life and reduce maintenance costs.
- Good soot dispersion that reduces oil consumption and wear.
- Balanced detergency/dispersancy that keeps engines cleaner.

TYPICAL PROPERTIES

Characteristic	40
SAE Grade	40
Specific Density @ 15°C	0.8800
Kinematic Viscosity @ 100°C, cSt	14.51
Viscosity Index	99
Colour, ASTM	L 3.0
Flash Point COC, °C	238
Total Base Number, mgKOH/g,	9

PACKAGING

200 Liter – Drum



DESCRIPTION

Jumbo SDX 50 CF-2 is heavy-duty diesel engine oil specially designed to lubricate diesel engines requiring API CF-2 classification.

APPLICATIONS

- Mixed fleets of diesel engines.
- Small diesel engines in marine services.
- Generator sets.

BENEFITS

- Oxidation stability that reduces sludge build up and viscosity increase.
- Effective anti-wear and anti-scuff properties that extend engine life and reduce maintenance costs.
- Good soot dispersion that reduces oil consumption and wear.
- Balanced detergency/dispersancy that keeps engines cleaner.

TYPICAL PROPERTIES

Characteristic	50
SAE Grade	50
Specific Density @ 15°C	0.8790
Kinematic Viscosity @ 40°C, cSt	177.50
Kinematic Viscosity @ 100°C, cSt	18.46
Viscosity Index	113
Colour, ASTM	L 3.0
Flash Point COC, °C	240

PACKAGING

200 Liter – Drum

